24-hour operation

TPS-50

Excellent Compact Pumps



Model	Output		Outlet		Pass Solid	Max	LPM Flow @ Head					Max	Dimension	Weight
	HP	W	mm	Inch	Dia(mm)	Flow(LPM)	1M	2M	3M	4M	5M	Head(M)	L × W × H (mm)	Kg
TPS-50	1/10	80	20	3/4"	5	40	38	33	20	-	-	4	114 x 114 x 265	2.5

Remarks: Model with "A" is equipped with wide angle float switch.

24-hour operation

TPS-200

Excellent Compact Pumps



Model	Output		Outlet		Pass Solid	Max	LPM Flow @ Head					Max	Dimension	Weight
	HP	W	mm	Inch	Dia(mm)	Flow(LPM)	1M	2M	3M	4M	5M	Head(M)	L × W × H (mm)	Kg
TPS-200	1/4	200	32	1-1/4"	5	140	135	120	100	80	55	7	168 x 146 x 288	3.6

Remarks: Model with "A" is equipped with wide angle float switch.

RS-E Series

Automatic ON/OFF Without Float Switch!



Model	Output		Outlet		Pass Solid	Max	LPM Flow @ Head					Max	Dimension	Weight
	HP	W	mm	Inch	Dia(mm)	Flow(LPM)	1.5M	3M	4.5M	6M	7.5M	Head(M)	L × W × H (mm)	Kg
RS-25E	1/6	100	25	1"	3	70	65	50	30	-	-	6	155 x 155 x 240	3.2
RS-32E	1/4	200	32	1-1/4"	3	130	125	100	65	30	-	7	155 x 155 x 240	4.2

Remarks: Optional for lower strainer.

24-hour operation

TPV-200

Dirty Water Usage
Solid Passage 19 mm



Model	Output		Outlet		Pass Solid	Max	LPM Flow @ Head					Max	Dimension	Weight
	HP	W	mm	Inch	Dia(mm)	Flow(LPM)	1M	2M	3M	4M	5M	Head(M)	L × W × H (mm)	Kg
TPV-200	1/4	200	32	1-1/4"	19	140	135	120	100	80	55	7	168 x 146 x 288	3.6

Remarks: Model with "A" is equipped with wide angle float switch.

RV-32 RV-40

RV Series

Solid Passage up to 18mm



Model	Output		Outlet		Pass Solid	Max	LPM Flow @ Head					Max	Dimension	Weight
	HP	W	mm	Inch	Dia(mm)	Flow(LPM)	1.5M	3M	4.5M	6M	7.5M	Head(M)	L × W × H (mm)	Kg
RV-32	1/4	200	32	1-1/4"	18	130	125	95	55	10	-	6.5	154 x 143 x 345	3.9
RV-40	1/3	250	32	1-1/4"	18	160	155	145	120	70	15	8	154 x 143 x 345	5.9

KS Series



Model	Output		Outlet		Pass solid	Max	LPM Flow @ Head					Max	Dimension	Weight
	HP	W	mm	inch	Dia(mm)	Flow(LPM)	3M	6M	9M	12M	15M	Head(M)	L × W × H (mm)	Kg
KS-03	1/3	250	40	1-1/2"	5	200	185	90	-	-	-	8	188 x 141 x 305	9
KS-04	1/2	400	50	2"	5	240	205	110	-	-	-	9	208 x 140 x 359	11
KS-05	1/2	400	50	2"	5	260	230	140	35	-	-	10	230 x 156 x 375	14
KS-10	1	750	50	2"	6	420	400	300	190	70	-	14	290 x 180 x 425	21
KS-20	2	1500	80	3"	9	620	590	490	360	200	40	16	278 x 182 x 475	31
		KW					5M	10M	15M	20M	25M			
KS-30	3	2.2	80	3"	11	900	800	530	250	-	-	18	390 x 250 x 450	42
KS-50	5	3.7	100	4"	11	1200	1130	920	630	220	-	22	450 x 240 x 530	48
KS-75	7.5	5.5	100	4"	11	1900	1750	1350	880	380	-	24	550 x 310 x 590	60
KS-100	10	7.5	150	6"	11	2400	2300	1350	1400	820	280	28	550 x 310 x 610	70

Remarks: Model with "A" is equipped with float switch.