

Technical data

Pump name

EVMG10 15F5/5.5

Customer	Date 05-June-2019	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail

Requested data

1	Pump type	VERTICAL PUMPS	Fluid	Water, clean
2	Number of pumps / Reserve	1 / 0	Liquid temperature °C	20
3	Flow m³/h	0	Kin. viscosity mm²/s	1
4	Head m	0	Vapour pressure bar	0.022
5	Static head m	0	PH value	7
6	Inlet pressure bar	0.1	Density kg/dm³	1
7	Available system NPSH	0	Solids Weight %	0
8	Environmental temperature °C	20		

Pump

9	Pump name	EVMG10 15F5/5.5	Frequency Hz	50
10	Design	VERTICAL PUMPS	Installation type	STANDARD
11	Manufacturer	EMC	Impeller	Max. mm 96
12	Speed 1/min	2850	Diameter	Designed mm 96
13	No. of Stage	15		Min. mm 96
14	Connection Suction side		Flow	Operating m³/h
15	Connection Discharge side			Max- m³/h 15
16	Max Working Pressure bar	25		Min- m³/h 4.5
17	Shut-off head bar	16.38	Head	Operating m
18	Total weight kg	See the table of "Dimensions".		- (Qmax.) m 68.1
19	Shaft power kW			- (Qmin.) m 162.5
20			Max. Shaft Power at max. impeller	kW 5.15
21	Required NPSH m		Efficiency	%

Materials

22	Impeller	AISI 304		
23	Intermediate casing	AISI 304		
24	Bottom casing	Cast Iron		
25	Shaft	AISI 316		
26				
27				

Motor

28	Manufacturer	LAFERT	Insulation class	F
29	Type	TEFC_EVM10 15F5/5.5_400_ Three Phase	Phases	3~
30	Specific design	IE2 / 50 Hz / Pole pairs 1	Frame size	132 S
31	Rated power kW	5.5	Weight kg	38.6
32	Number of poles	2	Electric voltage V	400
33	Speed 1/min	2900	Electric current A	10.4
34	Degree of protection	IP 55		
35				

Remarks

Performance curve

Pump name

EVMG10 15F5/5.5

Customer	Date 05-June-2019	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail

Requested data


1	Flow	m³/h	0
2	Head	m	0
3	Static head	m	0

Pump

Operating Flow	m³/h	Frequency	Hz	50
Operating Head	m	Number of poles	2	
Impeller Diameter	Designed mm	96	Speed	1/min

Test standard: ISO 9906:2012 - Grade3B


Water, clean [100%] ; 20°C; 0.9983kg/dm³; 1mm²/s



Dimensions

Pump name EVMG10 15F5/5.5

Customer	Date 05-June-2019	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail




Dimensions in mm							
1	A	Dia 300	H	80			
2	B	220	H2	764			
3	BF	Dia 12	H3	328			
4	BH	20	H8	21			
5	BL	190	SA	Dia 40			
6	BM	130	SG	Dia 79			
7	BW	250	SN	4			
8	BY 1	215	Weight kg	84.4			
9	C	161					
10	D1	Dia 110					
11	D2	Dia 150					
12	D3	Dia 18					
13	E	280					

(1/3) Construction

Pump name EVMG10 15F5

Customer	Date 05-June-2019	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail



(2/3) Construction

Pump name **EVMG10 15F5**

Customer	Date 05-June-2019	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail

N°	PART NAME	EVMG	MATERIAL EVM	EVML	DIMENSIONS	STANDARD	Q.TY
005-1	Suction casing	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			1
005-2	Intermediate casing	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			[1]
005-3	Intermediate casing bearing	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			[1]
005-4	Discharge casing	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			1
006	Bottom casing	Cast iron EN-GJL-200 -EN 1561	EN 1.4301(AISI 304)	EN 1.4401 (AISI 316)			1
007	Outer casing	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			1
021	Impeller	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			[1]
031	Shaft		EN 1.4401 (AISI 316)				1
043-1	Shaft sleeve (mechanical seal)	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			1
043-2	Shaft sleeve (intermediate)	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			[1]
043-3	Shaft sleeve (bearing)	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			[1]
043-5	Shaft sleeve (last stage)	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			[1]
044-1	Shaft sleeve bearing		Tungsten carbide				[1]
047	Ring holder	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			1
048	Impeller nut	A2-70 UNI 7323 with inox insert		A4-70 UNI 7323 with inox insert	M10		1
051	Motor adapter		Cast iron EN-GJL-200-EN 1561				[1]
052-1	Bearing		Tungsten carbide				[1]
056	Ball bearing		See table pag.357				[1]
075	O-ring (plug)		EPDM	FPM			1
075-1	O-ring (plug)	EVM, EVML EVMG	EPDM	FPM			2
107	Liner ring		PTFE/EN 1.4301(AISI 304)	PTFE/EN 1.4401 (AISI 316)			[1]
111	Mechanical seal		EPDM	Silicon carbide/Carbon/FPM			1
111-3	Mechanical seal seat	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			1
115-1	O-ring (outer casing)		EPDM	FPM	164.48x5.34	OR 6645	2
115-5	O-ring		EPDM	FPM	31.34x3.53	OR 4125	1
120-1	Tie rod		Zincate steel 6.8 strenght class ISO 898/1				4
120-3	Screw		A2-70 UNI 7323		M5x6	UNI 5931	4
120-6	Screw for coupling	EVM10 2/3/5/6 EVM10 8 to 20 EVM10 22	Zincate steel		M6x16 M8x20 M10x25	UNI 5931	[1]
120-8	Screw (motor adapter)		Zincate steel		M2x25	UNI 5739	[1]
120-13	Screw for motor	EVM10 2 to 3 EVM10 4 EVM10 5 to 11 EVM10 12 to 20 EVM10 22	Zincate steel 8.8 strenght class ISO 898/1		M6x16 M8x20 M8x30 M12x25 M16x65	UNI 5931 UNI 5739 UNI 5739 UNI 5739 UNI 5739	4
128-1	Nut for tie rod		Zincate steel		M12	UNI 5588	4
130-2	Screw for coupling guard		A2-70 UNI 7323		M5x6	UNI 7687	4
130-4	Set-screw		Carbon steel		M6x6	UNI 5929	[1]
131-1	Pin for shaft		Carbon steel				1
135-1	Washer		Zincate steel		13x24x2.5	UNI 6592	4
137-1	Impeller spacer	EN 1.4301(AISI 304)		EN 1.4401 (AISI 316)			1
140	Coupling	Other models EVM10 4 EVM10 22	Brass OT 58 UNI 5705 Die cast Aluminium EN AB-AISI11Cu2 (Fe) CF 35 SMn Pb10				1
150	Spacer		Carbon steel				[1]
162	Motor bracket	Cast iron EN-GJL-200 -EN 1561	Cast iron + EN 1.4301(AISI 304)	Cast iron + EN 1.4401 (AISI 316)			1
212	Plug		EN 1.4301(AISI 304)	EN 1.4401 (AISI 316)			1
212-1	Plug	EVM, EVML EVMG	EN 1.4301(AISI 304)	EN 1.4401 (AISI 316)			2
245	Coupling guard		EN 1.4301(AISI 304)				4
273	Washer (plug)		EN 1.4301(AISI 304)	EN 1.4401 (AISI 316)			2
273-1	Washer (plug)	EVM, EVML EVMG	EN 1.4301(AISI 304)	EN 1.4401 (AISI 316)			4
274-1	C-type snap ring (mechanical seal)		EN 1.4301(AISI 304)	EN 1.4401 (AISI 316)	D.16 JIS B2804-1978		1
274-2	C-type snap ring (coupling)	EVM10 5, EVM 10 6 EVM10 8 to 11 EVM10 12 to 20 EVM10 22	Carbon steel TC 80		D35 D40 D50 D65	UNI 7435	[1]
274-3	C-type snap ring (bracket)	EVM 10 5, EVM 10 6 EVM 10 8 to 11 EVM 10 12 to 20	Carbon steel TC 80		72 90 110	UNI 7437	[1]

[1] See table on CONSTRUCTION 3

(3/3) Construction

Pump name EVMG10 15F5

Customer	Date 05-June-2019	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail

Pump Type EVM(.)	Quantity for model																												
	005-2	005-3	021	043-2	043-3	043-5	044-1	051	052-1	056	Bearing type	070-1	107	115-3	117	120-5	120-6	120-7	120-8	120-11	128-3	128-6	130-4	135-4	135-6	150	219	274-2	274-3
10 6N5/2.2	3	1	5	3	1	1	1	1	1	1	6207 ZZ	/	5	2	2	/	2	/	/	4	/	/	1	/	/	1	2	1	1
10 6N5/2.2	4	1	6	4	1	1	1	1	1	1	6207 ZZ	/	6	2	2	/	2	/	/	4	/	/	1	/	/	1	2	1	1
10 8N5/3.0	6	1	8	6	1	1	1	1	1	1	6308 ZZ	/	8	2	2	/	2	/	/	4	/	/	1	/	/	1	2	1	1
10 10N5/4.0	8	1	10	8	1	1	1	1	1	1	6308 ZZ	/	10	2	2	/	2	/	/	4	/	/	1	/	/	1	2	1	1
10 11N5/4.0	9	2	11	9	1	1	1	1	1	1	6308 ZZ	/	11	2	2	/	2	/	/	4	/	/	1	/	/	1	2	1	1
10 12N5/5.5	9	2	12	9	2	1	2	1	2	1	6310 ZZ	/	12	2	2	/	2	/	4	4	/	/	1	/	/	1	2	1	1
10 14N5/5.5	11	2	14	11	2	1	2	1	2	1	6310 ZZ	/	14	2	2	/	2	/	4	4	/	/	1	/	/	1	2	1	1
10 15F5/5.5	12	2	15	12	2	1	2	1	2	1	6310 ZZ	/	15	/	/	/	2	/	4	/	/	/	1	/	/	1	/	1	1
10 16F5/7.5	13	2	16	13	2	1	2	1	2	1	6310 ZZ	/	16	/	/	/	2	/	4	/	/	/	1	/	/	1	/	1	1
10 18F5/7.5	15	2	18	15	2	1	2	1	2	1	6310 ZZ	/	18	/	/	/	2	/	4	/	/	/	1	/	/	1	/	1	1
10 20F5/7.5	17	2	20	17	2	1	2	1	2	1	6310 ZZ	/	20	/	/	/	2	/	4	/	/	/	1	/	/	1	/	1	1
10 22F5/11	19	2	22	19	2	1	2	1	2	1	6313 ZZ	1	22	/	/	/	2	3	4	/	4	/	1	3	/	1	/	1	1